

SPECIFICATION GUIDE

Trade Name:	Edgeline®
Species:	Radiata pine (<i>Pinus radiata</i>)
Sustainability:	FSC® mix, CoC No. SGS HK-COC-500007
Density:	450-500kg / m ³ seasoned
Moisture Content:	Kiln-dried to approx. 12% (+/- 3%)
Fire Hazard:	Group 3
Preservative Treatment:	Untreated
Formaldehyde Emissions:	<0.15mg/L (Super E0)
VOC Status:	No other volatile organic compounds
Finger Jointing:	Glued with VOC- and formaldehyde-free single component polyurethane adhesive
Coatings:	Finished with one coat of Gesso primer and one coat of water based acrylic primer. Will accept most oil and water based film forming coating systems
Intended Use:	Highly suited to installation in sheltered indoor locations protected from termite and fungal decay hazards. Should not be used in exterior applications, including under verandahs, patios and eaves
Finishing Recommendations:	Fill nail holes and wipe down surfaces to remove sawdust, dirt and other contaminants. Apply two coats of premium acrylic or enamel topcoat to clean and dry timber
In-Service Performance:	Will expand and contract with seasonal variations in moisture and humidity levels. Not recommended for areas that receive frequent wetting, such as in shower cubicles or bathroom splashbacks
Manufacturer's Warranty:	5 years against defects in materials and workmanship